



JAYCO SUPER SEAL UPGRADE

GREATLY IMPROVE THE SEALING PERFORMANCE OF ORIGINAL JAYCO VENT VALVES. THIS O-RING PLUNGER WITH JAYCO SUPER SEAL UPDATES THE SEALING PERFORMANCE TO WHAT CUSTOMERS HAVE COME TO EXPECT FROM JAYCO JT-8.1 THIEF HATCHES AND IS NOW STANDARD IN ALL NEW JAYCO VENT VALVES. 2 INCH P/N JV0110, 3 INCH P/N JV0311, 4 INCH P/N JV0510.

ADVANTAGES OF UPGRADING TO JAYCO SUPER SEAL PLUNGER

- GREATER SEALING PERFORMANCE
- EXCEEDS API2000 STANDARDS FOR ALLOWABLE LEAKAGE
- LESS THAN 0.5 SCFH @ 90% SET PRESSURE
- IMPROVES PRESSURE FLOW RATES
- UPGRADES ORIGINAL JAYCO VENT VALVES
- AVAILABLE FOR 2, 3, AND 4 INCH
- QUICK AND EASY REPLACEMENT
- NO TOOLS REQUIRED
- O-RING COMES STANDARD IN VITON®

INSTALLING NEW O-RING PLUNGER

1. REMOVE EXISTING PLUNGER
2. REMOVE CLIP-IN PRESSURE SEAT FROM THE BODY OF THE VALVE (WHERE THE PLUNGER SITS)
3. CLEAN THE ALUMINUM SURFACE THAT WAS HIDDEN BY THE PRESSURE SEAT FOR OPTIMUM SEAL
4. CAREFULLY LOWER THE O-RING PLUNGER INTO THE VALVE WITH THE GASKETS FACING DOWNWARD



VITON® IS A REGISTERED TRADEMARK OF DUPONT DOW ELASTOMERS

9412 NICHOLS ROAD • PO BOX 20026 • OKLAHOMA CITY, OK 73156

800-654-9263 • 405-751-6903 • FAX 405-755-7940 • WWW.JAYCO.ORG